Panasonic



TOUGHBOOK C2

- 12.5" Convertible Tablet with Multi Touch or Multi Touch + Digitizer Display
- Daylight-readable 500 Nit IPS Display
- Rugged Triple Hinge Design
- Full Shift Battery Life
- Bridge Battery Enables Hot-swap Battery Replacement for Continuous Use
- Available NFC, Bottom Camera, Serial Port, Barcode and SmartCard Readers^{1,2}

LONGEST STANDARD BATTERY LIFE IN ITS CLASS.

The Panasonic Toughbook® C2 provides an amazing 14 hours of battery life (19 hours with optional long life battery) and weighs 3.99 lbs. The 12.5" convertible tablet features an array of industry-leading advancements, such as being the only convertible tablet in its class to offer a durable triple hinge design, as well as a unique bridge battery for continuous use by enabling hot-swappable battery replacement without disruption.

The Toughbook C2 has an incredibly bright and sharp 500 nit IPS display with direct bonding for wider viewing angles and a lighter design. The ergonomic strap is perfect for long-term use and holding the PC in any orientation. Available integrated options, such as a barcode reader, SmartCard reader, NFC, bottom camera and serial port^{1,2}, make the Toughbook C2 ideal for a wide variety of applications and environments.



Panasonic

TOUGHBOOK C2

Panasonic recommends Windows.

| SOFTWARE | Windows® 8.1 Pro, Windows® 7 Professional Panasonic Utilities (including Dashboard), Recovery Partition | | |
|------------------|---|--|--|
| DURABILITY | 2.5' drop rating from 6 sides (1' from remaining sides) Spill-resistant keyboard Magnesium alloy case with hand strap Rugged triple hinge design Shock-mounted flex-connect hard drive with quick-release Pre-installed replaceable screen film for display protection | | |
| CPU | Intel® Core® i5-4300U vPro® Processor - 1.96Hz with Turbo Boost up to 2.9GHz - 3MB cache | | |
| STORAGE & MEMORY | 4GB or 8GB SDRAM (DDR3L)^{3,4} 500GB 7200rpm hard drive (shock-mounted flex-connect with quick-release)⁴ Optional 128GB and 256GB reinforced flex-connect SSD⁴ | | |
| DISPLAY | 12.5" HD 1366 x 768 with LED backlighting - 10-point capacitive multi touch + digitizer (with AR screen treatment) - 10-point capacitive multi touch (with AG screen treatment) 2-500 nit IPS display with direct bonding Ambient light, magnetic, gyro and acceleration sensors Automatic screen rotation Intel® HD Graphics 4400, max. 1792MB shared VRAM with Win 8.1 64-bit ⁵ Dual monitor support through HDMI and/or optional VGA Concealed mode (configurable) | | |
| AUDIO | Integrated microphone Intel® high-definition audio compliant Integrated speaker Keyboard volume and mute controls | | |
| KEYBOARD & INPUT | Touch and gestures Stylus pen with integrated stylus holder tablet buttons (2 user-definable) Dashboard 84-key with dedicated Windows® key Oversized electrostatic touchpad with multi touch support | | |
| CAMERAS | HD 1.3MP webcam with mic and camera on/off indicator Optional 5MP bottom camera with auto focus¹ | | |
| EXPANSION SLOTS | ExpressCard/34 ⁶ SD card (5DXC) | | |
| INTERFACE | ■ Docking connector 100-pin ■ HDMI Type A ■ Optional VGA² D-sub 15-pin ■ Headphones/speaker Mini-jack stereo ■ Microphone/line in Mini-jack stereo ■ Optional serial² D-sub 9-pin ■ USB 3.0 (x 2), USB 2.0 (x 1) 4-pin ■ 10/100/1000 Ethernet RJ-45 ■ Optional 56K Modem² RJ-11 | | |
| WIRELESS | Optional integrated 4G LTE multi carrier mobile broadband with satellite GPS Optional NFC (Near Field Communications)¹ Intel® Dual Band Wireless-N 7260 802.11a/b/g/n Bluetooth® v4.0 + EDR (Class 1) Security Authentication: LEAP, WPA, 802.1x, EAP-TLS, EAP-FAST, PEAP - Encryption: CKIP, TKIP, 128-bit and 64-bit WEP, Hardware AES Slide on/off switch | | |
| POWER SUPPLY | Li-lon battery pack with bridge battery: - Standard battery: 10.8V, typical 6800mAh, minimum 6400mAh - Long life battery: 10.8V, typical 9300mAh, minimum 8700mAh Battery operation?: - Standard battery: 14 hours - Long life battery: 19 hours - Bridge battery: 11 minute Battery charging time?: 2.5 hours off, 3 hours on (standard battery) 3 hours off, 3.5 hours on (long life battery) AC Adapter: AC 100V-240V 50/60Hz, auto sensing/switching worldwide power supply | | |

POWER MANAGEMENT

Suspend/Resume Function, Hibernation, Standby. ACPI BIOS

SECURITY FEATURES

- Password Security: Supervisor, User, Hard Disk Lock
- Kensington cable lock slot
- Trusted platform module (TPM) security chip v.1.2
- Computrace® theft protection agent in BIOS®
- Intel® Anti-Theft Technology
- Optional fingerprint reader
- Optional full and half-size SmartCard readers^{1,6}

WARRANTY

3-year limited warranty, parts and labor

DIMENSIONS & WEIGHT

- 8.4"(L) x 11.8"(W) x 1.0"/1.7"(H) front/rear
- 3.99 lbs. (standard battery)
- 4.28 lbs. (long life battery)

INTEGRATED OPTIONS9

- 4G LTE multi carrier mobile broadband with satellite GPS
- Choice of 1D/2D barcode reader (EA11 or EA21)² or Serial² or VGA² or Modem²
- Choice of half-size SmartCard¹, or NFC¹ or 5MP bottom camera¹
- Full-size SmartCard reader (not available with ExpressCard)⁶
- Fingerprint reader
- Long life battery
- 128GB and 256GB solid state drives (SSD)

SELECT ACCESSORIES

| ı | AC Adapter (3-prong) | CF-AA6413CM |
|---|-----------------------------|---------------|
| | Standard Battery Pack | CF-VZSU80U |
| | Long Life Battery Pack | CF-VZSU83U |
| | Battery Charger | CF-VCBTB3W |
| ı | LIND 3-Bay Battery Charger | CF-LND3BAYC2 |
| ı | LIND Car Adapter 120W | CF-LNDDC120 |
| | LIND O MONTH I CONTINUED IN | OF LAIDAODOOO |

CF-LNDACDC90 LIND Car/AC Adapter 90W (with USB port) ■ ToughMate C2 Convertible Case TBCC2CASE-P ■ ToughMate C2 Shoulder Strap TBCC2SSTP-P ■ ToughMate ComUniversal Carrying Case TBCCOMUNV-P

 ToughMate Backpack TRCRPK-P CF-WMBA1304G Memory Card 4GB DDR3 Desktop Dock with DVD Drive CF-VEBC21U Multi Touch Replacement Stylus CF-VNP020AU

■ Multi Touch + Digitizer Replacement Stylus CF-VNP016AU CF-VNT004U Tether ■ 12.5" LCD Protective Film CF-VPF25U

Please consult your reseller or Panasonic representative before purchasing. ¹Half-size SmartCard reader, NFC and 5MP bottom camera are mutually exclusive. ²Barcode reader, serial, VGA and modem ports are mutually exclusive

Total usable memory will be less depending upon actual system configuration.

41GB = 1,000,000,000 bytes.

*The size of the VRAM cannot be set by the user and varies by operating system as well as size of RAM. Windows 7 max. VRAM is 1696MB.

Field: size SmartCard reader and ExpressCard are mutually exclusive.

Approximate time. Battery performance features such as charge time and life span can vary according to the conditions under which the computer and battery are used. Battery operation and recharge times will vary based on many factors, including screen brighness, applications, features, power management, battery conditioning and other customer preferences. Battery testing results from MobileMark 2007.

⁸Requires software and activation to enable theft protection.

*Accessories and Integrated Options may vary depending on your notebook configuration. Visit Panasonic website for more accessories and details.







Battery status and bridge battery LED indicators